

Multi-service and Multi-tenant Application Delivery Controller Platform

XPoint VNF Manager allows customers to deploy ADC as Virtual Function through single-pane-of-management platform. XPoint VNF Manager makes it possible to seamlessly design feature rich managed load balancing services with agility and capacity on-demand.

The VNF-Manager-16 is a 2RU single-power appliance with 5Gbps throughput that supports 16 tenants.



Hardware Platform Specification

Performance	
Throughput (L4/L7)	6Gbps/5Gbps
SSL TPS (1K/2K Keys)	7,000/4,000
Concurrent Connections	3,500,000
Maximum Tenants	16
Network Interface	
Gigabit Copper	4
Gigabit Fiber	4
10GE Fiber	2
Hardware Specification	
Processor	Intel Quad Core
Memory (ECC RAM)	32GB
Storage	1TB SSD
ASIC SSL Hardware	N/A
Dimensions(W x D x H)	430mm (W) x 509mm (D) x 88mm (H)
Rack Units (Mountable)	2U
Unit Weight	20 kgs
Power Supply	2U 500W ATX AC Supply
Heat in BTU/hour	3,000
Operating Ranges	Temperature 0° - 40° C Humidity 10% - 85%

Authorized Distributor :



SecureHub Distribution Sdn Bhd (462057-H)

No: 7, Jalan 109E, Desa Business Park, Taman Desa,

Jalan Kelang Lama, 58100 Kuala Lumpur

Tel: 03-7983 6832 Fax: 03-7983 6687

Email: sales@securehub.com.my

SecureHub